




L'UNITE
HERMETIQUE



R-22

**RECIPROCATING AIR CONDITIONING
VERTICAL**

Compressor	Nominal Power (HP)	Displacement (CM ³)	Refrigerating Capacity (Watts)		
			-5°C	0°C	+7.2°C
AE5465E	1/2	12.00	928	1,170	1,572
AE5470E	3/5	13.30	1,000	1,268	1,716
AJ5510F	5/6	18.60	1,297	1,728	2,447
AJ5512E	1	21.75	1,662	2,130	2,909
AJ5513E	1 1/10	24.20	1,893	2,386	3,213
AJ/TAJ5515E	1 1/4	25.95	2,169	2,722	3,631
AJ5518E	1 1/2	32.70	2,771	3,436	4,563
AJ/TAJ5519E	1 4/7	34.45	2,894	3,587	4,779
FH/TFH5522F	1 5/6	40.80	3,059	3,955	5,483
FH/TFH5524F	2	43.90	3,309	4,279	5,929
FH/TFH5528F	2 1/3	49.00	3,852	4,950	6,811
FH/TFH5532F	2 2/3	53.08	4,327	5,540	7,619
FH/TFH5538F	3 1/6	67.50	5,384	6,848	9,353
FH/TFH5542F	3 1/2	74.15	5,645	7,215	9,951
TAG5546E	3 5/6	90.20	5,934	7,839	11,253
AG/TAG5553E	4 3/7	100.70	7,022	9,105	12,922
AG/TAG5561E	5	112.53	8,164	10,593	14,870
TAG5568E	5 2/3	124.40	9,180	11,862	16,676
TAG5573E	6	134.80	9,804	12,632	17,816
TAGD5590E	7 1/2	180.40	11,868	15,678	22,506
TAGD5610E	8 1/3	201.40	14,044	18,210	25,844
TAGD5612E	10	225.00	16,327	21,186	29,739
TAGD5614E	11 2/3	248.80	18,360	23,724	33,352
TAGD5615E	12 1/2	269.60	19,608	25,264	35,631